

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (currently amended) A system for regulation and discontinuous measurement of an oxygen content or a content of any other gas in platforms for composting or processing waste, in the form of swaths, the system comprising:

at least one remote bay having ~~at least one gas~~ measurement probe for measuring a concentration of a given gas and, the measurement probe being at least one oxygen or CO₂ measurement probe;

a gas intake pump;

electric valves operated by a program controller; and

a plastic pipe connecting each of the electric valves to a gas sampling device, the electric valves coupled to the pump allowing the air and the gases contained in this air at each sampling device to be drawn in successively and sent to the measurement probe;

wherein the sampling device is a ~~smooth~~ hollow sampling rod with ~~two opposite ends~~ an air intake strainer at one end able to be driven into the pile(s) of waste or compost, ~~[[;]]~~ a tube forming the rod, each one of the ~~smooth~~ hollow sampling rods corresponding to one single pipe, the pipe passing through the

hollow rod and ~~being fitted with an~~ emerging inside the air
intake strainer ~~at one end, the pipe being connected at the other~~
~~end of the rod,~~ and the oxygen measurement probe is able to
supply within a very short response time the measurement of the
oxygen content of several swaths and that consequently ~~this~~
oxygen measurement probe is a heated zirconium oxide sensor with
a response time less than ten seconds.

2. (previously presented) The system as in claim 1, wherein
the electric valves are separate from the program controller or
are integrated directly into the program controller.

3. (currently amended) The system as in ~~one of the claims in~~
~~1 or 2~~ claim 1, wherein [[the]] attachment of the rod to the pipe
uses a packing gland facilitating [[the]] fastening or insertion
of the pipe.

4. (currently amended) The system as in claim [[3]] 1,
wherein a single gas measurement probe, in particular oxygen or
CO₂ can be used to measure, respectively, the oxygen or CO₂
content of several swaths by means of samples obtained from the
various gas sampling rods.

5 (currently amended) The system as in claim [[4]] 1,
wherein the program controller further comprising at least one

temperature probe attachable to at least one input/output port enabling [[it]] the program controller to receive PT 100 or PT 1000- type signals for temperature measurement.

6. (currently amended) The system as in claim [[5]] 1, wherein the rod for sampling air in the waste, and used for measuring the concentration of oxygen, CO₂ or any other gas, does not contain a sensor or a transmitter built into [[the]] a body of the rod, but only the intake strainer and ~~its respective~~ the pipe.

7. (currently amended) The system as in claim [[6]] 1, wherein the gas intake pump ~~being~~ is equipped with a device for regulating [[the]] a flow of air to the probe(s), [[of]] or a rotameter.

8. (currently amended) The system as in claim 1, wherein the air-sampling rod contains, at one ~~of its ends~~ end, the intake strainer and, at [[the]] an other end, a packing gland ~~enabling insertion of the pipe for sampling the air in the compost or waste~~ providing effective sealing between the hollow rod and the plastic pipe and holds the plastic pipe in place.

9. (currently amended) A gas measurement system for sampling and measuring gas content in piles or platforms of composting or

processing waste, in the form of swaths, the gas measurement system comprising:

at least one remote bay having at least one gas measurement probe, the gas measurement probe being a heated zirconium oxide sensor, the gas measurement probe being in communication with a program controller;

a gas intake pump;

at least one electric valve operated by the program controller; and

at least one plastic pipe connected the electric valve to a ~~smooth~~ hollow rod, the electric valve being coupled to the pump allowing the air and the gases contained in the air at the ~~smooth~~ hollow rod to be drawn in successively and sent to the gas measurement probe;

wherein the ~~smooth~~ hollow rod ~~having~~ has a first end able to be driven into the pile of waste or compost, the first end of the hollow rod being fitted with a tapered air intake strainer, and a second end opposite of the first end ~~and attachable to a free end of the pipe in which the plastic pipe passes through the hollow rod to emerge inside the strainer, the plastic pipe being fastened and sealed to the hollow rod~~ by means of a packing gland, the first end of the smooth rod being fitted with a tapered air intake strainer;

wherein the program controller having at least one temperature probe and at least one input/output port enabling the

program controller to receive PT 100 or PT 1000-type signals for temperature measurement or other signals for measuring other gases present.

10. (previously presented) The gas measurement system as in claim 9, further comprising a main bay in communication with the program controller of the remote bay via a bus.

11. (previously presented) The gas measurement system as in claim 9, wherein the gas intake pump being equipped with a device for regulating the flow of air to the gas measurement probe, the gas measurement probe being a rotameter.

12. (currently amended) The system as in claim 1, wherein the air intake ~~filter~~ strainer is tapered.